



NOTE:


1. THE CONTRACTOR SHALL REFER TO THE MANUFACTURER FOR CONSTRUCTION MATERIALS AND SPECIFICATIONS FOR "KOR-N-SEAL" INSTALLATION.
2. 12 INCH MINIMUM SPACING BETWEEN MANHOLE JOINT AND KOR.



KORBAND




CONNECTOR



PIPE CLAMP

Connector P/N	Suggested Pipe O.D. Range (in inches)	Hole/Connector Dimensions (in inches)				Pipe Clamp P/N
		A	B	C	D	
S106-7	3.50 to 4.50	7	6.125	4.500	6	M-80
S406-10 1/2A	6.00 to 6.75	10.5	9.375	6.500	6	M-128
S406-10 1/2	7.50 to 9.00	10.5	9.375	8.500	6	M-180
S106-12B	5.75 to 7.00	12	10.875	6.500	8	M-128
S106-12A	7.00 to 8.50	12	10.875	8.000	8	M-180
S106-12	8.25 to 9.75	12	10.875	9.250	8	M-180
S406-12C	6.00 to 7.00	12	10.875	6.500	6	M-128
S406-12B	6.25 to 7.50	12	10.875	7.000	6	M-128
S406-12A	7.50 to 9.00	12	10.875	8.500	6	M-180
S406-12	9.00 to 10.50	12	10.875	10.000	6	M-180
S106-16B	9.50 to 11.25	16	14.875	10.500	8	M-192
S106-16A	11.25 to 13.00	16	14.875	12.250	8	M-240
S106-16	13.00 to 14.50	16	14.875	14.000	8	M-240



CHARLES COUNTY GOVERNMENT

DEPARTMENT OF PLANNING & GROWTH MANAGEMENT

APPROVED: Raymond N. Shumaker, Jr. Aug 8, 2023  
Raymond N. Shumaker, Jr. (Aug 8, 2023 12:00 EDT)  
 CHIEF OF CODES, PERMITS, & INSPECTION SERVICES DATE

A.P.B. Aug 8, 2023  
Apply 6:00 PM (Aug 8, 2023 14:40 EDT)  
 PROFESSIONAL ENGINEER DATE

STANDARD DETAIL

KOR-N-SEAL

S  
1.07

REVISIONS: