



ELEVATION

NOTES

1. FOR PAVED AREAS SEE CLEANOUT COVER ASSEMBLY DETAIL. CLEANOUTS IN SIDEWALKS AND DRIVEWAYS ARE APPROVED ON A CASE BY CASE BASIS.
2. VERTICAL CLEANOUT RISER STUB SHALL BE 4 FEET OR LESS BELOW SURFACE FOR UNIMPROVED LOTS AND PROVIDED WITH A WATER TIGHT PLUG. LOCATION IS TO BE MARKED WITH A 2"x6" BOARD EXTENDING ONE FOOT MIN. ABOVE GRADE.
3. A FLEXIBLE COUPLING WILL BE REQUIRED BETWEEN THE MAIN AND THE CLEANOUT WYE BRANCH IF THE WYE IS A DIFFERENT MATERIAL THAN THE PIPE.
4. IF A PVC WYE IS USED. IT SHALL BE SET ON ITS SIDE WITH TWO 45 DEGREE BENDS WITH A SHORT SPOOL PIECE BETWEEN THE BENDS.

STANDARD SYMBOL — SHC ●



CHARLES COUNTY GOVERNMENT

DEPARTMENT OF PLANNING & GROWTH MANAGEMENT

APPROVED: Raymond N. Shumaker, Jr. Aug 8, 2023
Raymond N. Shumaker, Jr. (Aug 8, 2023 12:00 EDT)

CHIEF OF CODES, PERMITS, & INSPECTION SERVICES DATE

Andy B. Mills Aug 8, 2023
Andy B. Mills (Aug 8, 2023 14:40 EDT)

PROFESSIONAL ENGINEER DATE

STANDARD DETAIL

STANDARD CLEAN-OUT
 NON-TRAFFIC AREA

S
 4.03

REVISIONS:
 DECEMBER 2022