



NOTES:

- PAVEMENT - ASPHALT = SEE TABLE 2.07 OF ROAD ORDINANCE
CONCRETE = 7" THICK FOR RESIDENTIAL, 8" THICK FOR COMMERCIAL.
6"X6" W2.9XW2.9 WIRE MESH OR #3 REINFORCING BARS 12" O.C. BOTH WAYS, WITH MINIMUM 4" COMPACTED BANK RUN GRAVEL BASE COURSE, EXPANSION JOINTS MINIMUM 100' ON CENTER. SCORE THE CONCRETE TO A DEPTH OF 1/3 THE SLAB THICKNESS FOR WEAKENED PLANE TRANSVERSE JOINTS AT 10' MINIMUM INTERVALS.
- CROSS-SECTION MAY BE MODIFIED TO DRAIN TO ONE SIDE AS SHOWN ON PLAN.

CHARLES COUNTY GOVERNMENT

DEPARTMENT OF PLANNING & GROWTH MANAGEMENT

APPROVED: *[Signature]* 2/27/11

CHIEF OF CODES, PERMITS, & INSPECTION SERVICES

DATE

[Signature] 7-27-11

HIGHWAY ENGINEER

DATE

STANDARD DETAIL

ALLEY

REVISIONS:

R
2.51